					DEPARTMEN ^T	T OF NA	OF UTAH ATURAL RES GAS AND M				AMEN	F NDED REPO	ORM 3 DRT	
		AF	PPLICATION	FOR PE	RMIT TO DRILL					1. WELL NAME and N		3-4-9-17		
2. TYPE O	F WORK	DRILL NEW WELL	REENT	ER P&A W	/ELL DEEPEN	N WELL [)			3. FIELD OR WILDCAT MONUMENT BUTTE				
4. TYPE O	F WELL				Methane Well: NO					5. UNIT or COMMUNITIZATION AGREEMENT NAME GMBU (GRRV)				
6. NAME OF OPERATOR NEWFIELD PRODUCTION COMPANY										7. OPERATOR PHONE 435 646-4825				
8. ADDRESS OF OPERATOR Rt 3 Box 3630 , Myton, UT, 84052														
	AL LEASE NUN L, INDIAN, OR S	TATE)		11	. MINERAL OWNERS	SHIP DIAN) STATE () FEE		12. SURFACE OWNER		STAT	_	EE (
13. NAME	OF SURFACE	UTU-75038 OWNER (if box 12	= 'fee')				7 0	J(14. SURFACE OWNER	~	•		
15. ADDR	ESS OF SURFA	CE OWNER (if box	12 = 'fee')							16. SURFACE OWNER	R E-MAI	L (if box 1	2 = 'fee')	
17. INDIA	N ALLOTTEE O	R TRIBE NAME			B. INTEND TO COMM		PRODUCTIO	N FROM		19. SLANT				
(if box 12	? = 'INDIAN')				ULTIPLE FORMATIO YES (Submit C		gling Applicat	ion) NO 🗓	2	VERTICAL DIF	RECTION	IAL 📵	HORIZON ⁻	TAL 🔵
20. LOC/	ATION OF WELI	L		FOOT	AGES	QT	TR-QTR	SECTI	ION	TOWNSHIP	F	RANGE	МІ	ERIDIAN
LOCATIO	ON AT SURFAC	E	19	949 FNL	1988 FWL		SENW	4		9.0 S	1	17.0 E		S
Top of U	Top of Uppermost Producing Zone 658 FNL 1				1981 FWL	١	NENW	4		9.0 S	1	17.0 E		S
At Total	Depth		6	58 FNL	1981 FWL	١	NENW	4		9.0 S		17.0 E		S
21. COUNTY DUCHESNE 22. DISTANCE TO NEAREST LEASE LINE (Feet) 658									23. NUMBER OF ACRI		RILLING U 40	NIT		
25. DISTANCE TO NEAREST WE (Applied For Drilling or Compl								E POOL		26. PROPOSED DEPTI		TVD: 63	80	
27. ELEV	ATION - GROUP	ND LEVEL 5164		28	B. BOND NUMBER		000493			29. SOURCE OF DRILLING WATER / WATER RIGHTS APPROVAL NUMBER IF APPLICABLE 437478				LE
					Hole, Casing	g, and C	Cement Info	ormation						
String Surf	Hole Size	Casing Size 8.625	Length 0 - 300	Weigh 24.0			Max Mud			Cement Class G		Sacks 138	Yield 1.17	Weight 15.8
Prod	7.875	5.5	0 - 6530	15.5			8.3		Prem	ium Lite High Stren	ath	313	33.26	11.0
										50/50 Poz		363	1.24	14.3
		,			A	ATTACH	HMENTS							
VERIFY THE FOLLOWING ARE ATTACHED IN ACCORDANCE WITH THE UTAH OIL AND GAS CONSERVATION GENERAL RULES														
✓ w	ELL PLAT OR M	IAP PREPARED BY	LICENSED SUR	VEYOR O	OR ENGINEER		№ cow	IPLETE DRIL	LING PI	_AN				
AF	FIDAVIT OF ST	ATUS OF SURFACE	OWNER AGRE	EMENT (I	F FEE SURFACE)		FOR	M 5. IF OPER	ATOR IS	S OTHER THAN THE LE	EASE OV	VNER		
DIRECTIONAL SURVEY PLAN (IF DIRECTIONALLY OR HORIZONTALLY DRILLED)								OGRAPHICA	L MAP					
NAME Mandie Crozier TITLE Regulatory Tech									PHOI	NE 435 646-4825				
SIGNATU	JRE				DATE 01/23/201	4			ЕМА	IL mcrozier@newfield.c	com			
	BER ASSIGNED				APPROVAL				J	Myzon				
									Pe	rmit Manager				

NEWFIELD PRODUCTION COMPANY GMBU 3-4-9-17 AT SURFACE: SE/NW SECTION 4, T9S R17E DUCHESNE COUNTY, UTAH

TEN POINT DRILLING PROGRAM

1. **GEOLOGIC SURFACE FORMATION:**

Uinta formation of Upper Eocene Age

2. <u>ESTIMATED TOPS OF IMPORTANT GEOLOGIC MARKERS:</u>

Uinta 0' - 3,750' Green River 3,750' Wasatch 6,230'

Proposed TD 6,530'(MD) 6,380' (TVD)

3. ESTIMATED DEPTHS OF ANTICIPATED WATER, OIL, GAS OR MINERALS:

Green River Formation (Oil) 3,750' – 6,230'

Fresh water may be encountered in the Uinta Formation, but would not be expected below about 350'. All water shows and water bearing geologic units shall be reported to the geologic and engineering staff of the Vernal Office prior to running the next string of casing or before plugging orders are requested. All water shows must be reported within one (1) business day after being encountered.

All usable (<10,000 PPM TDS) water and prospectively valuable minerals (as described by BLM at onsite) encountered during drilling will be recorded by depth and adequately protected. This information shall be reported to the Vernal Office.

Detected water flows shall be sampled, analyzed, and reported to the geologic & engineering staff of the Vernal Office. The office may request additional water samples for further analysis. Usage of the State of Utah form *Report of Water Encountered* is acceptable, but not required.

The following information is requested for water shows and samples where applicable:

Location & Sampled Interval Date Sampled Flow Rate Temperature

Hardness pH

Water Classification (State of Utah)

Dissolved Calcium (Ca) (mg/l)

Dissolved Iron (Fe) (ug/l)

Dissolved Sodium (Na) (mg/l)

Dissolved Carbonate (CO₃) (mg/l)

Dissolved Bicarbonate (NaHCO₃) (mg/l)

Dissolved Sulfate (SO₄) (mg/l)

Dissolved Total Solids (TDS) (mg/l)

RECEIVED: January 23, 2014

4. PROPOSED CASING PROGRAM

a. Casing Design: GMBU 3-4-9-17

Size	lı	nterval	Maiabt	Grade	Counling	Design Factors		
Size	Тор	Bottom	Weight	Grade	Coupling	Burst	Collapse	Tension
Surface casing	0'	2001	04.0	J-55	STC	2,950	1,370	244,000
8-5/8"	U	300' 24.0 J-55 ST		310	17.53	14.35	33.89	
Prod casing	O'	6 F20'	45.5	J-55	1.70	4,810	4,040	217,000
5-1/2"	0'	6,530'	,530' 15.5		LTC	2.32	1.94	2.14

Assumptions:

- 1) Surface casing max anticipated surface press (MASP) = Frac gradient gas gradient
- 2) Prod casing MASP (production mode) = Pore pressure gas gradient
- 3) All collapse calculations assume fully evacuated casing w/ gas gradient
- 4) All tension calculations assume air weight

Frac gradient at surface casing shoe = 13.0 ppg
Pore pressure at surface casing shoe = 8.33 ppg
Pore pressure at prod casing shoe = 8.33 ppg
Gas gradient = 0.115 psi/ft

All casing shall be new or, if used, inspected and tested. Used casing shall meet or exceed API standards for new casing.

All casing strings shall have a minimum of 1 (one) centralizer on each of the bottom three (3) joints.

b. Cementing Design: GMBU 3-4-9-17

Job	Fill	Description	Sacks ft ³	OH Excess*	Weight (ppg)	Yield (ft³/sk)	
Surface casing	300'	Class G w/ 2% CaCl	138	30%	15.8	1.17	
			161				
Prod casing	4,530'	Prem Lite II w/ 10% gel + 3%	313	30%	11.0	3.26	
Lead	4,530	KCI	1020	30%	11.0	3.26	
Prod casing	2,000'	50/50 Poz w/ 2% gel + 3%	363	30%	14.3	1.24	
Tail	2,000	KCI	451	30%	14.3	1.24	

^{*}Actual volume pumped will be 15% over the caliper log

- Compressive strength of lead cement: 1800 psi @ 24 hours, 2250 psi @ 72 hours
- Compressive strength of tail cement: 2500 psi @ 24 hours

Hole Sizes: A 12-1/4" hole will be drilled for the 8-5/8" surface casing. A 7-7/8" hole will be drilled for the 5-1/2" production casing.

The 8-5/8" surface casing shall in all cases be cemented back to surface. In the event that during the primary surface cementing operation the cement does not circulate to surface, or if the cement level should fall back more than 8 feet from surface, then a remedial surface cementing operation shall be performed to insure adequate isolation and stabilization of the surface casing.

5. <u>MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL</u>:

The operator's minimum specifications for pressure control equipment are as follows:

An 8" Double Ram Hydraulic unit with a closing unit will be utilized. Function test of BOP's will be check daily.

Refer to Exhibit C for a diagram of BOP equipment that will be used on this well.

6. TYPE AND CHARACTERISTICS OF THE PROPOSED CIRCULATION MUDS:

From surface to ±300 feet will be drilled with an air/mist system. The air rig is equipped with a 6 ½" blooie line that is straight run and securely anchored. The blooie line is used with a discharge less than 100 ft from the wellbore in order to minimize the well pad size. The blooie line is not equipped with an automatic igniter or continuous pilot light and the compressor is located less than 100 ft from the well bore due to the low possibility of combustion with the air dust mixture. The trailer mounted compressor (capacity of 2000 CFM) has a safety shut-off valve which is located 15 feet from the air rig. A truck with 70 bbls of water is on stand by to be used as kill fluid, if necessary. From about ±300 feet to TD, a fresh water system will be utilized. Clay inhibition and hole stability will be achieved with a KCl substitute additive. This additive will be identified in the APD and reviewed to determine if the reserve pit shall be lined. This fresh water system will typically contain Total Dissolved Solids (TDS) of less than 3000 PPM. Anticipated mud weight is 8.4 lbs/gal. If necessary to control formation fluids or pressure, the system will be weighted with the addition of bentonite gel, and if pressure conditions warrant, with barite

No chromate additives will be used in the mud system on Federal and/or Indian lands without prior BLM approval to ensure adequate protection of fresh aquifers.

No chemicals subject to reporting under SARA Title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of this well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported, or disposed of in association with the drilling, testing, or completing of this well.

Hazardous substances specifically listed by the EPA as a hazardous waste or demonstrating a characteristic of a hazardous waste will not be used in drilling, testing, or completion operations.

Newfield Production will **visually** monitor pit levels and flow from the well during drilling operations.

7. **AUXILIARY SAFETY EQUIPMENT TO BE USED:**

Auxiliary safety equipment will be a Kelly Cock, bit float, and a TIW valve with drill pipe threads.

8. <u>TESTING, LOGGING AND CORING PROGRAMS</u>:

The logging program will consist of a Dual Induction, Gamma Ray and Caliper log from TD to base of surface casing @ 300' +/-, and a Compensated Neutron-Formation Density Log from TD to 3500' +-. A cement bond log will be run from PBTD to cement top. No drill stem testing or coring is planned for this well.

9. <u>ANTICIPATED ABNORMAL PRESSURE OR TEMPERATURE</u>:


No abnormal temperatures or pressures are anticipated. No hydrogen sulfide has been encountered or is known to exist from previous drilling in the area at this depth. Maximum anticipated


bottomhole pressure will approximately equal total depth in feet multiplied by a $0.433~\mathrm{psi/foot}$ gradient.


10. ANTICIPATED STARTING DATE AND DURATION OF THE OPERATIONS:


It is anticipated that the drilling operations will commence the third quarter of 2014, and take approximately seven (7) days from spud to rig release.


RECEIVED: January 23, 2014











Well Number			
	Feature Type	Latitude (NAD 83) (DMS)	Longitude (NAD 83) (DMS
6-4-9-17	Surface Hole	40° 03′ 42.38" N	110° 00' 50.02" W
G-4-9-17	Surface Hole	40° 03' 42.17" N	110° 00' 50.00" W
N-4-9-17	Surface Hole	40° 03' 41.96" N	110° 00' 49.99" W
3-4-9-17	Surface Hole	40° 03′ 42.59" N	110° 00' 50.03" W
3-4-9-17	Bottom of Hole	40° 03' 55.34" N	110° 00' 50.09" W
Well Number	Feature Type	Latitude (NAD 83) (DD)	Longitude (NAD 83) (DD)
6-4-9-17	Surface Hole	40.061772	110.013894
G-4-9-17	Surface Hole	40.061714	110.013889
N-4-9-17	Surface Hole	40.061656	110.013885
3-4-9-17	Surface Hole	40.061831	110.013898
3-4-9-17	Bottom of Hole	40.065373	110.013913
Well Number	Feature Type	Northing (NAD 83) (UTM Meters)	Longitude (NAD 83) (UTM Me
6-4-9-17	Surface Hole	4435079.160	584098.549
G-4-9 - 17	Surface Hole	4435072.707	584099.015
N-4-9-17	Surface Hole	4435066.266	584099.438
3-4-9-17	Surface Hole	4435085.643	584098.123
3-4-9-17	Bottom of Hole	4435478.832	584092.480
Well Number	Feature Type	Latitude (NAD 27) (DMS)	Longitude (NAD 27) (DMS
6-4-9-17	Surface Hole	40° 03' 42.51" N	110° 00' 47.48" W
G-4-9-17	Surface Hole	40° 03' 42.30" N	110° 00' 47.46" W
N-4-9-17	Surface Hole	40° 03' 42.10" N	110° 00' 47.45" W
3-4-9-17	Surface Hole	40° 03' 42.72" N	110° 00' 47.50" W
3-4-9-17	Bottom of Hole	40° 03' 55.48" N	110° 00' 47.55" W
Well Number	Feature Type	Latitude (NAD 27) (DD)	Longitude (NAD 27) (DD
6-4-9-17	Surface Hole	40.061810	110.013189
G-4-9-17	Surface Hole	40.061751	110.013184
N-4-9-17	Surface Hole	40.061693	110.013180
3-4-9-17	Surface Hole	40.061868	110.013193
3-4-9-17	Bottom of Hole	40.065411	110.013208



NEWFIELD EXPLORATION COMPANY

Existing 6-4-9-17 Pad Proposed Well: 3-4-9-17 Sec. 4, T9S, R17E, S.L.B.&M. Duchesne County, UT.

DRAWN BY:	A.P.C.	REVISED:
DATE:	12-13-2013	
VERSION:	V2	

COORDINATE REPORT

SHEET

1

Coordinate Report									
Well Number	Feature Type	Northing (NAD 27) (UTM Meters)	Longitude (NAD 27) (UTM Mete						
6-4-9-17	Surface Hole	4434873.839	584160.837						
G-4-9-17	Surface Hole	4434867.385	584161.303						
N-4-9-17	Surface Hole	4434860.945	584161.726						
3-4-9-17	Surface Hole	4434880.322	584160.411						
3-4-9-17	Bottom of Hole	4435273.510	584154.765						
	1								



NEWFIELD EXPLORATION COMPANY

Existing 6-4-9-17 Pad Proposed Well: 3-4-9-17 Sec. 4, T9S, R17E, S.L.B.&M. Duchesne County, UT.

DRAWN BY:	A.P.C.	REVISED:
DATE:	12-13-2013	
VERSION:	V2	

COORDINATE REPORT

SHEET

2



NEWFIELD EXPLORATION

USGS Myton SW (UT) SECTION 4 T9S R17E 3-4-9-17

Wellbore #1

Plan: Design #1

Standard Planning Report

15 January, 2014





Payzone Directional

Planning Report



 Database:
 EDM 5000.1 Single User Db

 Company:
 NEWFIELD EXPLORATION

 Project:
 USGS Myton SW (UT)

 Site:
 SECTION 4 T9S R17E

 Well:
 3-4-9-17

 Wellbore:
 Wellbore #1

 Design:
 Design #1

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well 3-4-9-17

3-4-9-17 @ 5174.0usft (PLAN) 3-4-9-17 @ 5174.0usft (PLAN)

True

Minimum Curvature

Project USGS Myton SW (UT), DUCHESNE COUNTY, UT, USA

Map System: US State Plane 1983

Geo Datum: North American Datum 1983

Map Zone: Utah Central Zone

System Datum: Mean Sea Level

Site SECTION 4 T9S R17E

Northing: 7,194,100.00 usft Site Position: Latitude: 40° 3' 36.542 N From: Lat/Long Easting: 2,057,000.00 usft Longitude: 110° 0' 41.593 W **Position Uncertainty:** 0.0 usft Slot Radius: 13-3/16 " **Grid Convergence:** 0.95

Well 3-4-9-17, SHL: 40* 03' 42.59" -110* 00' 50.03"

 Well Position
 +N/-S
 611.9 usft
 Northing:
 7,194,700.94 usft
 Latitude:
 40° 3′ 42.590 N

 +E/-W
 -656.0 usft
 Easting:
 2,056,333.95 usft
 Longitude:
 110° 0′ 50.030 W

Position Uncertainty0.0 usftWellhead Elevation:5,174.0 usftGround Level:5,164.0 usft

Wellbore Wellbore #1 Magnetics **Model Name** Sample Date Declination **Dip Angle** Field Strength (nT) (°) (°) IGRF2010 1/15/2014 10.96 65.75 52,034

Design #1 Design **Audit Notes:** Version: Phase: **PROTOTYPE** Tie On Depth: 0.0 **Vertical Section:** Depth From (TVD) +N/-S +E/-W Direction (usft) (usft) (usft) (°) 0.0 0.0 0.0 359.79

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
600.0	0.00	0.00	600.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,508.1	13.62	359.79	1,499.6	107.4	-0.4	1.50	1.50	0.00	359.79	
6,529.8	13.62	359.79	6,380.0	1,290.1	-4.7	0.00	0.00	0.00	0.00	3-4-9-17 TGT



Payzone Directional

Planning Report



Database: EDM 5000.1 Single User Db
Company: NEWFIELD EXPLORATION
Project: USGS Myton SW (UT)
Site: SECTION 4 T9S R17E

 Well:
 3-4-9-17

 Wellbore:
 Wellbore #1

 Design:
 Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well 3-4-9-17

3-4-9-17 @ 5174.0usft (PLAN) 3-4-9-17 @ 5174.0usft (PLAN)

True

Minimum Curvature

Design:	Design #1								
Planned Survey									
riailileu Suivey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
+00.0	0.00							0.00	
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	1.50	359.79	700.0	1.3	0.0	1.3	1.50	1.50	0.00
800.0	3.00	359.79	799.9	5.2	0.0	5.2	1.50	1.50	0.00
900.0	4.50	359.79	899.7	11.8	0.0	11.8	1.50	1.50	0.00
1 000 0	6.00	250.70	000.3	20.0	0.1	20.0	1.50	1.50	0.00
1,000.0	6.00	359.79	999.3	20.9	-0.1	20.9	1.50	1.50	0.00
1,100.0	7.50	359.79	1,098.6	32.7	-0.1	32.7	1.50	1.50	0.00
1,200.0	9.00	359.79	1,197.5	47.0	-0.2	47.0	1.50	1.50	0.00
1,300.0	10.50	359.79	1,296.1	64.0	-0.2	64.0	1.50	1.50	0.00
1,400.0	12.00	359.79	1,394.2	83.5	-0.3	83.5	1.50	1.50	0.00
1,508.1	13.62	359.79	1,499.6	107.4	-0.4	107.4	1.50	1.50	0.00
1,600.0	13.62	359.79	1,588.9	129.1	-0.5	129.1	0.00	0.00	0.00
1,700.0	13.62	359.79	1,686.1	152.6	-0.6	152.6	0.00	0.00	0.00
							0.00	0.00	
1,800.0	13.62	359.79	1,783.3	176.2	-0.6	176.2 199.7		0.00	0.00
1,900.0	13.62	359.79	1,880.4	199.7	-0.7		0.00		0.00
2,000.0	13.62	359.79	1,977.6	223.3	-0.8	223.3	0.00	0.00	0.00
2,100.0	13.62	359.79	2,074.8	246.8	-0.9	246.8	0.00	0.00	0.00
2,200.0	13.62	359.79	2,172.0	270.4	-1.0	270.4	0.00	0.00	0.00
2,300.0	13.62	359.79	2,269.2	293.9	-1.1	293.9	0.00	0.00	0.00
2,400.0	13.62	359.79	2,366.4	317.5	-1.1	317.5	0.00	0.00	0.00
2,500.0	13.62	359.79	2,463.6	341.0	-1.2	341.0	0.00	0.00	0.00
2,600.0	13.62	359.79	2,560.8	364.6	-1.3	364.6	0.00	0.00	0.00
2,700.0	13.62	359.79	2,657.9	388.1	-1.4	388.1	0.00	0.00	0.00
								0.00	0.00
2,800.0	13.62	359.79	2,755.1	411.7	-1.5	411.7	0.00		
2,900.0	13.62	359.79	2,852.3	435.2	-1.6	435.2	0.00	0.00	0.00
3,000.0	13.62	359.79	2,949.5	458.8	-1.7	458.8	0.00	0.00	0.00
3,100.0	13.62	359.79	3,046.7	482.3	-1.7	482.3	0.00	0.00	0.00
3,200.0	13.62	359.79	3,143.9	505.9	-1.8	505.9	0.00	0.00	0.00
3,300.0	13.62	359.79	3,241.1	529.4	-1.9	529.4	0.00	0.00	0.00
3,400.0	13.62	359.79	3,338.3	553.0	-2.0	553.0	0.00	0.00	0.00
3 500 0	12.62	250.70	2 425 4	576 5	2.1	576 F	0.00	0.00	0.00
3,500.0	13.62	359.79	3,435.4	576.5	-2.1	576.5	0.00	0.00	0.00
3,600.0	13.62	359.79	3,532.6	600.1	-2.2	600.1	0.00	0.00	0.00
3,700.0	13.62	359.79	3,629.8	623.6	-2.3	623.7	0.00	0.00	0.00
3,800.0	13.62	359.79	3,727.0	647.2	-2.3	647.2	0.00	0.00	0.00
3,900.0	13.62	359.79	3,824.2	670.7	-2.4	670.8	0.00	0.00	0.00
4,000.0	13.62	359.79	3,921.4	694.3	-2.5	694.3	0.00	0.00	0.00
4,100.0	13.62	359.79	4,018.6	717.9	-2.6	717.9	0.00	0.00	0.00
4,200.0	13.62	359.79	4,115.8	741.4	-2.7	741.4	0.00	0.00	0.00
4,300.0	13.62	359.79	4,212.9	765.0	-2.8	765.0	0.00	0.00	0.00
4,400.0	13.62	359.79	4,310.1	788.5	-2.9	788.5	0.00	0.00	0.00
4,500.0	13.62	359.79	4,407.3	812.1	-2.9	812.1	0.00	0.00	0.00
4,600.0	13.62	359.79	4,504.5	835.6	-3.0	835.6	0.00	0.00	0.00
4,700.0	13.62	359.79	4,601.7	859.2	-3.1	859.2	0.00	0.00	0.00
4,800.0	13.62	359.79	4,698.9	882.7	-3.2	882.7	0.00	0.00	0.00
4,900.0	13.62	359.79	4,796.1	906.3	-3.3	906.3	0.00	0.00	0.00
5,000.0	13.62	359.79	4,893.2	929.8	-3.4	929.8	0.00	0.00	0.00
5,100.0	13.62	359.79	4,990.4	953.4	-3.4	953.4	0.00	0.00	0.00
5,200.0	13.62	359.79	5,087.6	976.9	-3.5	976.9	0.00	0.00	0.00
5,300.0	13.62	359.79	5,184.8	1,000.5	-3.6	1,000.5	0.00	0.00	0.00
5,500.0	10.02	555.13	5, 107.0	1,000.0	-0.0	1,000.0	0.00	0.00	0.00



Payzone Directional

Planning Report



Database: EDM 5000.1 Single User Db
Company: NEWFIELD EXPLORATION
Project: USGS Myton SW (UT)
Site: SECTION 4 T9S R17E

 Well:
 3-4-9-17

 Wellbore:
 Wellbore #1

 Design:
 Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Well 3-4-9-17

3-4-9-17 @ 5174.0usft (PLAN) 3-4-9-17 @ 5174.0usft (PLAN)

True

Minimum Curvature

lanned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,400.0	13.62	359.79	5,282.0	1,024.0	-3.7	1,024.0	0.00	0.00	0.00
5,500.0	13.62	359.79	5,379.2	1,047.6	-3.8	1,047.6	0.00	0.00	0.00
5,600.0	13.62	359.79	5,476.4	1,071.1	-3.9	1,071.1	0.00	0.00	0.00
5,700.0	13.62	359.79	5,573.6	1,094.7	-4.0	1,094.7	0.00	0.00	0.00
5,800.0	13.62	359.79	5,670.7	1,118.2	-4.0	1,118.2	0.00	0.00	0.00
5,900.0	13.62	359.79	5,767.9	1,141.8	-4.1	1,141.8	0.00	0.00	0.00
6,000.0	13.62	359.79	5,865.1	1,165.3	-4.2	1,165.3	0.00	0.00	0.00
6,100.0	13.62	359.79	5,962.3	1,188.9	-4.3	1,188.9	0.00	0.00	0.00
6,200.0	13.62	359.79	6,059.5	1,212.4	-4.4	1,212.4	0.00	0.00	0.00
6,300.0	13.62	359.79	6,156.7	1,236.0	-4.5	1,236.0	0.00	0.00	0.00
6,400.0	13.62	359.79	6,253.9	1,259.5	-4.6	1,259.5	0.00	0.00	0.00
6,500.0	13.62	359.79	6,351.1	1,283.1	-4.6	1,283.1	0.00	0.00	0.00
6,529.8	13.62	359.79	6,380.0	1,290.1	-4.7	1,290.1	0.00	0.00	0.00

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
3-4-9-17 TGT - plan hits target c - Circle (radius 75.		0.00	6,380.0	1,290.1	-4.7	7,195,990.77	2,056,307.85	40° 3' 55.340 N	110° 0' 50.090 W

API Well Number: 43013528050000 Project: USGS Myton SW (UT)



Site: SECTION 4 T9S R17É


Well: 3-4-9-17 Wellbore: Wellbore #1 Design: Design #1


KOP @ 600' DOGLEG RATE 1.5 DEG/100 TARGET RADIUS IS 75'




Azimuths to True North Magnetic North: 10.96°

Magnetic Field Strength: 52033.6snT Dip Angle: 65.75° Date: 1/15/2014 Model: IGRF2010









SECTION DETAILS +N/-S 0.0 0.0 107.4 1290.1 +E/-W 0.0 0.0 -0.4 -4.7 TVD 0.0 600.0 1499.6 6380.0 Sec MD Inc 1 0.0 0.00 2 600.0 0.00 3 1508.1 13.62 4 6529.8 13.62 TFace VSect Target
0.00 0.0
0.00 0.0
359.79 107.4
0.00 1290.1 3-4-9-17 TGT

NEWFIELD PRODUCTION COMPANY GMBU 3-4-9-17 AT SURFACE: SE/NW SECTION 4, T9S, R17E DUCHESNE COUNTY, UTAH

ONSHORE ORDER NO. 1

MULTI-POINT SURFACE USE & OPERATIONS PLAN

1. EXISTING ROADS

See attached Topographic Map "A"

To reach Newfield Production Company well location site GMBU 3-4-9-17 located in the SE 1/4 NW 1/4 Section 4, T9S, R17E, Duchesne County, Utah:

Proceed southwesterly out of Myton, Utah along Highway 40 - 1.4 miles \pm to the junction of this highway and UT State Hwy 53; proceed southeasterly -10.7 miles \pm to it's junction with an existing road to the west; proceed in a westerly direction -0.3 miles \pm to it's junction with the beginning of the access road to the existing 6-4-9-17 well location.

The aforementioned dirt oil field service roads and other roads in the vicinity are constructed out of existing native materials that are prevalent to the existing area they are located in and range from clays to a sandy-clay shale material.

The roads for access during the drilling, completion and production phase will be maintained at the standards required by the State of Utah, or other controlling agencies. This maintenance will consist of some minor grader work for smoothing road surfaces and for snow removal. Any necessary fill material for repair will be purchase and hauled from private sources.

2. PLANNED ACCESS ROAD

There is no proposed access road for this location. The proposed well will be drilled directionaly off of the existing 6-4-9-17 well pad. See attached **Topographic Map "B"**.

There will be **no** culverts required along this access road. There will be barrow ditches and turnouts as needed along this road.

There are no fences encountered along this proposed road. There will be no new gates or cattle guards required.

All construction material for this access road will be borrowed material accumulated during construction of the access road.

3. LOCATION OF EXISTING WELLS

Refer to Exhibit "B".

4. LOCATION OF EXISTING AND/OR PROPOSED FACILITIES

There are no existing facilities that will be used by this well.

It is anticipated that this well will be a producing oil well.

Upon construction of a tank battery, the well pad will be surrounded by a dike of sufficient capacity to contain at minimum 110% of the largest tank volume within the facility battery.

Tank batteries will be built to State specifications.

All permanent (on site for six (6) months or longer) structures, constructed or installed (including pumping units), will be painted a flat, non-reflective, earth tone color to match one of the standard environmental colors, as determined by the Rocky Mountain Five State Interagency Committee. All facilities will be painted within six months of installation.

5. <u>LOCATION AND TYPE OF WATER SUPPLY</u>

Newfield Production will transport water by truck from nearest water source as determined by a Newfield representative for the purpose of drilling the above mentioned well. The available water sources are as follows:

Johnson Water District Water Right: 43-7478

Maurice Harvey Pond Water Right: 47-1358

Neil Moon Pond

Water Right: 43-11787

Newfield Collector Well

Water Right: 47-1817 (A30414DVA, contracted with the Duchesne County Conservancy

District).

There will be no water well drilled at this site.

6. <u>SOURCE OF CONSTRUCTION MATERIALS</u>

All construction material for this location shall be borrowed material accumulated during construction of the location site and access road.

A mineral material application is not required for this location.

7. METHODS FOR HANDLING WASTE DISPOSAL

A small reserve pit (90' x 40' x 8' deep, or less) will be constructed from native soil and clay materials. The reserve pit will receive the processed drill cutting (wet sand, shale & rock) removed from the wellbore. Any drilling fluids, which do accumulate in the pit as a result of shale-shaker carryover, cleaning of the sand trap, etc., will be promptly reclaimed. All drilling fluids will be fresh water based, typically containing Total Dissolved Solids of less than 3000 PPM. No potassium chloride, chromates, trash, debris, nor any other substance deemed hazardous will be placed in this pit. Therefore, it is proposed that no synthetic liner be required in the reserve pit. However, if upon constructing the pit there is insufficient fine clay and silt present, a liner will be used for the purpose of reducing water loss through percolation.

Newfield requests approval that a flare pit not be constructed or utilized on this location.

A portable toilet will be provided for human waste.

A trash basket will be provided for garbage (trash) and hauled away to an approved disposal site at the completion of the drilling activities.

8. <u>ANCILLARY FACILITIES</u>

There are no ancillary facilities planned for at the present time and none foreseen in the near future.

9. WELL SITE LAYOUT

See attached Location Layout Sheet.

Fencing Requirements

- All pits will be fenced or have panels installed consistent with the following minimum standards:
 - 1. The wire shall be no more than two (2) inches above the ground. If barbed wire is utilized it will be installed three (3) inches above the net wire. Total height of the fence shall be at least forty-two (42) inches.
 - Corner posts shall be centered and/or braced in such a manner to keep tight and upright at all times
 - 3. Standard steel, wood or pipe posts shall be used between the corner braces. Maximum distance between any two posts shall be no greater than sixteen (16) feet.

The reserve pit fencing will be on three (3) sides during drilling operations and on the fourth side when the rig moves off location. Pits will be fenced and maintained until cleanup.

Existing fences to be crossed by the access road will be braced and tied off before cutting so as to prevent slacking in the wire. The opening shall be closed temporarily as necessary during construction to prevent the escape of livestock, and upon completion of construction the fence shall be repaired to BLM specifications.

10. PLANS FOR RESTORATION OF SURFACE:

a) Producing Location

Immediately upon well completion, the location and surrounding area will be cleared of all unused tubing, equipment, debris, material, trash and junk not required for production.

The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the approximated natural contours. Weather permitting, the reserve pit will be reclaimed within one hundred twenty (120) days from the date of well completion. Before any dirt work takes place, the reserve pit must have all fluids and hydrocarbons removed.

b) Dry Hole Abandoned Location

At such time as the well is plugged and abandoned, the operator shall submit a subsequent report of abandonment and the State of Utah will attach the appropriate surface rehabilitation conditions of approval.

11. <u>SURFACE OWNERSHIP</u> – Bureau of Land Management.

12. OTHER ADDITIONAL INFORMATION

The Archaeological Resource Survey and Paleontological Resource Survey for this area are attached. State of Utah Antiquities Project (Survey) Permit No. U-13-MQ-0824bs, 10/2/13, prepared by Montgomery Archaeological Consultants. Paleontological Resource Survey prepared by, Wade Miller, 9/25/13. See attached report cover pages, Exhibit "D".

Water Disposal

After first production, if the production water meets quality guidelines, it will be transported to the Ashley, Monument Butte, Jonah, South Wells Draw and Beluga water injection facilities by company or contract trucks. Subsequently, the produced water is injected into approved Class II wells to enhance Newfield's secondary recovery project. Water not meeting quality criteria, will be disposed at Newfield's Pariette #4 disposal well (Sec. 7, T9S R19E), Federally approved surface disposal facilities or at a State of Utah approved surface disposal facilities.

Additional Surface Stipulations

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws and regulations, Onshore Oil and Gas Orders, the approved plan of operations and any applicable Notice to Lessees. A copy of these conditions will be furnished to the field representative to ensure compliance.

Hazardous Material Declaration

Newfield Production Company guarantees that during the drilling and completion of the GMBU 3-4-9-17, Newfield will not use, produce, store, transport or dispose 10,000# annually of any of the hazardous chemicals contained in the Environmental Protection Agency's consolidated list of chemicals subject to reporting under Title III Superfund Amendments and Reauthorization Act (SARA) of 1986. Newfield also guarantees that during the drilling and completion of the GMBU 3-4-9-17, Newfield will use, produce, store, transport or dispose less than the threshold planning quantity (T.P.Q.) of any extremely hazardous substances as defined in 40 CFR 355.

A complete copy of the approved APD, if applicable, shall be on location during the construction of the location and drilling activities.

Newfield Production Company or a contractor employed by Newfield Production shall contact the State office at (801) 722-3417, 48 hours prior to construction activities.

13. <u>LESSEE'S OR OPERATOR'S REPRENSENTATIVE AND CERTIFICATION:</u>

Representative

Name: Corie Miller

Address: Newfield Production Company

Route 3, Box 3630 Myton, UT 84052

Telephone: (435) 646-3721


<u>Certification</u>

Please be advised that NEWFIELD PRODUCTION COMPANY is considered to be the operator of well #3-4-9-17, Section 4, Township 9S, Range 17E: Lease UTU-75038 Duchesne County, Utah: and is responsible under the terms and conditions of the lease for the operations conducted upon the leased lands. Bond coverage is provided by, Federal Bond #WYB000493.


I hereby certify that the proposed drill site and access route have been inspected, and I am familiar with the conditions which currently exist; that the statements made in this plan are true and correct to the best of my knowledge; and that the work associated with the operations proposed here will be performed by Newfield Production Company and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of the 18 U.S.C. 1001 for the filing of a false statement.


1/23/14	
Date	Mandie Crozier
	Regulatory Analyst
	Newfield Production Company

Typical 2M BOP stack configuration



2M CHOKE MANIFOLD EQUIPMENT - CONFIGURATION OF CHOKES MAY VARY





NEWFIELD EXPLORATION COMPANY CROSS SECTIONS EXISTING 6-4-9-17 PAD PROPOSED WELL: 3-4-9-17 Pad Location: SENW Section 4, T9S, R17E, S.L.B.&M. 30, Н 1" = 60'STA. 3+30 PROPOSED **EXPANSION** AREA 30, Ш 1" = 60'STA. 2+20 **FINISHED** EXISTING GRADE GRADE 30, PROPOSED Ш WELL HEAD 1" = 60'STA. 1+55 30, \parallel 1" = 60'STA. 0+00 ESTIMATED EARTHWORK QUANTITIES (No Shrink or swell adjustments have been used) (Expressed in Cubic Yards) Note: This location will require ±540 yards of material to be imported to Construct Design. Borrow area & material to be 6" TOPSOIL ITEM CUT FILL **EXCESS** PAD 200 1,430 Topsoil is not included -1,230 NOTE: approved by Landowner and the Operator. UNLESS OTHERWISE PIT 690 0 in Pad Cut 690 NOTED ALL CUT/FILL **TOTALS** 890 1,430 400 -540 SLOPES ARE AT 1.5:1

SURVEYED BY: S.H.	DATE SURVEYED:	08-13-13	VERSION:	1 /Tri State (435) 781-2501
DRAWN BY: M.W.	DATE DRAWN:	12-13-13	\/2	Land Surveying, Inc.
SCALE: $1'' = 60'$	REVISED:		٧Z	180 NORTH VERNAL AVE. VERNAL, UTAH 84078

NEWFIELD EXPLORATION COMPANY TYPICAL RIG LAYOUT EXISTING 6-4-9-17 PAD PROPOSED WELL: 3-4-9-17 Pad Location: SENW Section 4, T9S, R17E, S.L.B.&M. Existing Access Road STORAGE TANK YELLOW DOG BOILER 🗀 15, □ TOILET PUMP TRAILERS 139* PIPE RACKS PIPE RACKS

SURVEYED	BY: S.H.	DATE SURVEYED:	08-13-13	VERSION:	
DRAWN BY	∕₃ M.W.	DATE DRAWN:	12-13-13	1/2	
SCALE:	1" = 60'	REVISED:		VZ	\angle


 $egin{array}{lll} egin{array}{lll} egin{array}{lll} Tri & State & ext{(435) 781-2501} \ Land & Surveying, & Inc. \end{array}$

NEWFIELD EXPLORATION COMPANY

RECLAMATION LAYOUT

EXISTING 6-4-9-17 PAD PROPOSED WELL: 3-4-9-17

Pad Location: SENW Section 4, T9S, R17E, S.L.B.&M.



Notes

1. Reclaimed Area to Include Seeding of Approved Vegetation and Sufficient Storm Water Management System.

2. Actual Equipment Layout and Reclaimed Pad Surface Area May Change due to Production Requirements or Site Conditions.

DISTURBED AREA:

TOTAL DISTURBED AREA = ± 2.56 ACRES TOTAL RECLAIMED AREA = ± 1.67 ACRES UNRECLAIMED AREA = ± 0.89 ACRES

SURVEYED BY:	S.H.	DATE SURVEYED:	08-13-13	VERSION:	$\wedge T$
DRAWN BY:	M.W.	DATE DRAWN:	12-13-13	1/2	/ T.
SCALE: 1"	= 60'	REVISED:		VZ	

Tri State (435) 781-2501
Land Surveying, Inc.
180 NORTH VERNAL AVE. VERNAL, UTAH 84078


NEWFIELD EXPLORATION COMPANY

PROPOSED SITE FACILITY DIAGRAM

6-4-9-17 PAD 3-4-9-17 UTU-75038

Pad Location: SENW Section 4, T9S, R17E, S.L.B.&M.


Duchesne County, Utah



<u>Legend</u>

NOT TO SCALE

SURVEYED BY:	S.H.	DATE SURVEYED:	08-13-13	VERSION:	/Tri State
DRAWN BY:	M.W.	DATE DRAWN:	12-13-13	1/2	/ Land Surveying, Inc.
SCALE:	NONE	REVISED:		٧Z	180 NORTH VERNAL AVE. VERNAL, UTAH 84078



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Utah State Office 440 West 200 South, Suite 500 Salt Lake City, UT 84101

IN REPLY REFER TO: 3160 (UT-922)

January 27, 2014

Memorandum

To: Assistant Field Office Manager Minerals,

Vernal Field Office

From: Michael Coulthard, Petroleum Engineer

Subject: 2014 Plan of Development Greater Monument

Butte Unit, Duchesne and Uintah Counties,

Utah.

Pursuant to email between Diana Mason, Division of Oil, Gas and Mining, and Mickey Coulthard, Utah State Office, Bureau of Land Management, the following wells are planned for calendar year 2014 within the Greater Monument Butte Unit, Duchesne and Uintah Counties, Utah.

API # WELL NAME LOCATION

(Proposed PZ GREEN RIVER)

43-013-52782 GMBU 122-8-9-17 Sec 08 T09S R17E 1875 FSL 1954 FWL BHL Sec 08 T09S R17E 1823 FSL 2526 FEL 43-013-52798 GMBU T-29-8-17 Sec 28 T08S R17E 0629 FSL 0503 FWL BHL Sec 29 T08S R17E 1575 FSL 0094 FEL Sec 04 T09S R17E 1949 FNL 1988 FWL BHL Sec 04 T09S R17E 0658 FNL 1981 FWL 43-013-52805 GMBU 3-4-9-17 43-013-52806 GMBU 4-3-9-17 Sec 04 T09S R17E 0704 FNL 0822 FEL BHL Sec 03 T09S R17E 0660 FNL 0660 FWL 43-013-52807 GMBU 2-4-9-17 Sec 04 T09S R17E 0683 FNL 0824 FEL BHL Sec 04 T09S R17E 0660 FNL 1980 FEL Sec 34 T085 R17E 0694 FSL 1971 FWL BHL Sec 03 T095 R17E 0660 FNL 1980 FWL 43-013-52808 GMBU 3-3-9-17

Notes: The surface location was erroneously stated on the APD cover submitted to the Utah Division of Oil, Gas and Mining. All other information remained the same. Please see our memo dated 1/23/2014.


This office has no objection to permitting the wells at this time.

bcc: File - Greater Monument Butte Unit Division of Oil Gas and Mining Central Files
Agr. Sec. Chron Fluid Chron

MCoulthard:mc:1-27-14

STATE OF UTAH							F UTAH					Ю	RM 3		
DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING										AMENDED REPORT					
		AF	PLICATION	FOR F	PERMIT	T TO DRILL					1. WELL NAME and NUMBER GMBU 122-8-9-17				
2. TYPE OF WORK DRILL NEW WELL () REENTER P&A WELL () DEEPEN WELL ()									3. FIELD OR WILDCAT MONUMENT BUTTE						
4. TYPE OF WELL									5. UNIT OF COMMUNITIZATION AGREEMENT NAME GMBU (GRRV)						
Oil Well Coalbed Methane Well:NO 6. NAME OF OPERATOR										7. OPERATOR PHONE					
NEWFIELD PRODUCTION COMPANY 8. ADDRESS OF OPERATOR								435 646-4825 9. OPERATOR E-MAIL							
40 MINES	AL LEASE NUM	DED	Rt 3 Box 36			, 84052 ERAL OWNERS	· IIID						ewfield.co	m	
	AL LEASE NUM _, INDIAN, OR S					RAL INDI	-	STATE () FE	E 🔘	12. SURFACE OWNER FEDERAL IND	ATT-	STATE	FE	E 🔘
13. NAME	OF SURFACE	OWNER (if box 12	= 'fee')								14. SURFACE OWNER	R PHONE	(if box 12	= 'fee')	
15. ADDR	ESS OF SURFA	CE OWNER (if box	12 = 'fee')								16. SURFACE OWNE	R E-MAIL	(if box 12	= 'fee')	
17. INDIAI	N ALLOTTEE OF	R TRIBE NAME				END TO COMM		RODUCTION	FRON	1	19. SLANT				
	! = 'INDIAN')				YES (OLE FORMATION		ling Applicati	on) NC	• •	VERTICAL DIF	RECTIONA	т 🌘 н	ORIZONT	AL 🔘
20. LOC	ATION OF WELL	낸		FO	OTAGES	s	QT	R-QTR	s	ECTION	TOWNSHIP	R	ANGE	ME	RIDIAN
LOCATIO	N AT SURFACE	i i	1	875FSL	L1954FW	VL	N	IESW		8	9.08	1	7.0E		S
Top of U	ppermost Prod	ucing Zone	1	858FSL	L2380FWL N		NESW		8	8 9.0S		17.0E		S	
At Total	Depth		1	1823FSI	SL2526FEL N		WSE		8	9.08		17.0E		s	
21. COUN	ITY	DUCHESNE			22. DIST	TANCE TO NEA	REST LE		eet)		23. NUMBER OF ACR	ES IN DR		T	
						TANCE TO NEA									
27. ELEV	ATION - GROUN	D LEVEL 5341			28. BON	8. BOND NUMBER WYB000493				29. SOURCE OF DRILLING WATER / WATER RIGHTS APPROVAL NUMBER IF APPLICABLE 437478					
		5341			1	Hole, Casing			rmati	on		437	470		
String	Hole Size	Casing Size	Length	We	ight	Grade & Th		Max Mu	111000000000000000000000000000000000000	1	Cement		Sacks	Yield	Weight
SURF	12.25	8.625	0 - 300	24	1.0	J-55 ST8	kC	8.3			Class G		138	1.17	15.8
PROD	7.875	5.5	0 - 6013	15	5.5	J-55 LT8	kC	8.3		Pren	nium Lite High Strer	ngth	277	3.26	11.0
											50/50 Poz		363	1.24	14.3
						A	TTACH	MENTS							
	VER	IFY THE FOLLO	WING ARE A	TTAC	HED IN	N ACCORDAN	ICE WIT	TH THE UTA	H OIL	AND GAS	CONSERVATION G	ENERA	L RULES	9	
WELL PLAT OR MAP PREPARED BY LICENSED SURVEYOR OR ENGINEER															
AF	FIDAVIT OF STA	TUS OF SURFACE	OWNER AGRE	EMENT	T (IF FEE	E SURFACE)		FORM	1 5. IF C	OPERATOR I	S OTHER THAN THE LI	EASE OW	NER		
✓ DIF	RECTIONAL SUI	RVEY PLAN (IF DIR	ECTIONALLY	OR HO	RIZONT	ALLY DRILLED)	торо	GRAPI	HICAL MAP					
NAMEMa	ındie Crozier			TITLER	Regulator	ry Tech				PHONE 435	646-4825				
SIGNATU	IRE			DATE 0	1/16/20	014			7	EMAILmcro	zier@newfield.com				
ADI NIMBED ASSIGNED 430.12527820000 ADDROVAL															

Received: January 24, 2014



Received: January 16, 2014

API Well Number: 4301352805000 ton sw (UT) Site: SECTION 8 T9S, R17E Well: 122-8-9-17

Wellbore: Wellbore #1 Design: Design #1




Azimuths to True North Magnetic North: 10.99°

Magnetic Field Strength: 52037.1snT Dip Angle: 65.74° Date: 11/11/2013 Model: IGRF2010



KOP @ 600' DOGLEG RATE 1.5 DEG/100 TARGET RADIUS IS 75'



API Well Number: 43013528050000 sw (UT)

NEWFIELD

Site: SECTION 28 T8S, R17E


Well: T-29-8-17

Well: T-29-8-17
Wellbore: Wellbore #1
Design: Design #1



Azimuths to True North Magnetic North: 11.03°

> Magnetic Field Strength: 52088.8snT Dip Angle: 65.78° Date: 8/5/2013 Model: IGRF2010




API Well Number: 4301352805090 Myton SW (UT)
Site: SECTION 4 T9S R17E
Well: 3-4-9-17 NEWFIELD

Wellbore: Wellbore #1 Design: Design #1

Azimuths to True North Magnetic North: 10.96°

Magnetic Field Strength: 52033.6snT Dip Angle: 65.75° Date: 1/15/2014 Model: IGRF2010

KOP @ 600' DOGLEG RATE 1.5 DEG/100 TARGET RADIUS IS 75'



API Well Number: 4301352805090 Myton SW (UT)
Site: SECTION 4 T9S R17E
Well: 4-3-9-17 NEWFIELD


Wellbore: Wellbore #1 Design: Design #1



Azimuths to True North Magnetic North: 10.96°

Magnetic Field Strength: 52037.1snT Dip Angle: 65.76° Date: 1/15/2014 Model: IGRF2010

KOP @ 600' DOGLEG RATE 1.5 DEG/100 TARGET RADIUS IS 75'



API Well Number: 4301352805000 Mton SW (UT)

Site: SECTION 4 19S R17E

Well: 2-4-9-17


Wellbore: Wellbore #1

Design: Design #1 NEWFIELD

Azimuths to True North Magnetic North: 10.96°

Magnetic Field Strength: 52037.1snT Dip Angle: 65.76° Date: 1/15/2014 Model: IGRF2010

KOP @ 600' DOGLEG RATE 1.5 DEG/100 TARGET RADIUS IS 75'



API Well Number: 43013528050000 sw (UT)

Site: SECTION 34 T8S, R17E

Well: 3-3-9-17

Wellibore: Wellbore: #1 NEWFIELD


Design: Design #1

KOP @ 600' DOGLEG RATE 1.5 DEG/100 TARGET RADIUS IS 75'



Azimuths to True North Magnetic North: 10.96°

Magnetic Field Strength: 52040.8snT Dip Angle: 65.76° Date: 1/15/2014 Model: IGRF2010



API Well Number: 43013528050000

WORKSHEET APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 1/23/2014 API NO. ASSIGNED: 43013528050000

WELL NAME: GMBU 3-4-9-17

OPERATOR: NEWFIELD PRODUCTION COMPANY (N2695) **PHONE NUMBER:** 435 646-4825

CONTACT: Mandie Crozier

PROPOSED LOCATION: SENW 04 090S 170E Permit Tech Review:

> SURFACE: 1949 FNL 1988 FWL **Engineering Review:**

> BOTTOM: 0658 FNL 1981 FWL Geology Review:

COUNTY: DUCHESNE

LATITUDE: 40.06182 LONGITUDE: -110.01386

UTM SURF EASTINGS: 584101.00 NORTHINGS: 4435084.00

FIELD NAME: MONUMENT BUTTE LEASE TYPE: 1 - Federal

LEASE NUMBER: UTU-75038 PROPOSED PRODUCING FORMATION(S): GREEN RIVER

SURFACE OWNER: 1 - Federal **COALBED METHANE: NO**

RECEIVED AND/OR REVIEWED: LOCATION AND SITING:

✓ PLAT R649-2-3.

Unit: GMBU (GRRV) Bond: FEDERAL - WYB000493

Potash R649-3-2. General

Oil Shale 190-5

Oil Shale 190-3 R649-3-3. Exception

Oil Shale 190-13 **Drilling Unit**

Board Cause No: Cause 213-11 Water Permit: 437478

Effective Date: 11/30/2009 **RDCC Review:**

Siting: Suspends General Siting Fee Surface Agreement

Intent to Commingle ■ R649-3-11. Directional Drill

Commingling Approved

Comments: Presite Completed

Stipulations: 4 - Federal Approval - dmason

15 - Directional - dmason

27 - Other - bhill



State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

Permit To Drill

Well Name: GMBU 3-4-9-17 **API Well Number:** 43013528050000

Lease Number: UTU-75038 Surface Owner: FEDERAL Approval Date: 1/28/2014

Issued to:

NEWFIELD PRODUCTION COMPANY, Rt 3 Box 3630, Myton, UT 84052

Authority:

Pursuant to Utah Code Ann. 40-6-1 et seq., and Utah Administrative Code R649-3-1 et seq., the Utah Division of Oil, Gas and Mining issues conditions of approval, and permit to drill the listed well. This permit is issued in accordance with the requirements of Cause 213-11. The expected producing formation or pool is the GREEN RIVER Formation(s), completion into any other zones will require filing a Sundry Notice (Form 9). Completion and commingling of more than one pool will require approval in accordance with R649-3-22.

Duration:

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date

General:

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

Conditions of Approval:

State approval of this well does not supercede the required federal approval, which must be obtained prior to drilling.

In accordance with Utah Admin. R.649-3-11, Directional Drilling, the operator shall submit a complete angular deviation and directional survey report to the Division within 30 days following completion of the well.

Production casing cement shall be brought up to or above the top of the unitized interval for the Greater Monument Butte Unit (Cause No. 213-11).

Notification Requirements:

The operator is required to notify the Division of Oil, Gas and Mining of the following actions during drilling of this well:

• Within 24 hours following the spudding of the well - contact Carol Daniels at 801-538-5284

(please leave a voicemail message if not available) OR

submit an electronic sundry notice (pre-registration required) via the Utah Oil & Gas website

at http://oilgas.ogm.utah.gov

Reporting Requirements:

All reports, forms and submittals as required by the Utah Oil and Gas Conservation General Rules will be promptly filed with the Division of Oil, Gas and Mining, including but not limited to:

- Entity Action Form (Form 6) due within 5 days of spudding the well
- Monthly Status Report (Form 9) due by 5th day of the following calendar month
 - Requests to Change Plans (Form 9) due prior to implementation
 - Written Notice of Emergency Changes (Form 9) due within 5 days
- Notice of Operations Suspension or Resumption (Form 9) due prior to implementation
 - Report of Water Encountered (Form 7) due within 30 days after completion
- Well Completion Report (Form 8) due within 30 days after completion or plugging

Approved By:

For John Rogers Associate Director, Oil & Gas Sundry Number: 59800 API Well Number: 43013528050000

STATE OF UTAH			FORM 9	
	DEPARTMENT OF NATURAL RESOURCE DIVISION OF OIL, GAS, AND MINI	5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-75038		
SUNDRY NOTICES AND REPORTS ON WELLS			6. IF INDIAN, ALLOTTEE OR TRIBE NAME:	
	oposals to drill new wells, significantly d reenter plugged wells, or to drill horizon n for such proposals.		7.UNIT or CA AGREEMENT NAME: GMBU (GRRV)	
1. TYPE OF WELL Oil Well			8. WELL NAME and NUMBER: GMBU 3-4-9-17	
2. NAME OF OPERATOR: NEWFIELD PRODUCTION CO	OMPANY		9. API NUMBER: 43013528050000	
3. ADDRESS OF OPERATOR: Rt 3 Box 3630 , Myton, UT		PHONE NUMBER: Ext	9. FIELD and POOL or WILDCAT: MONUMENT BUTTE	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1949 FNL 1988 FWL			COUNTY: DUCHESNE	
QTR/QTR, SECTION, TOWNSI Qtr/Qtr: SENW Section: (HIP, RANGE, MERIDIAN: 04 Township: 09.0S Range: 17.0E Meridi	an: S	STATE: UTAH	
11. CHEC	K APPROPRIATE BOXES TO INDICATI	E NATURE OF NOTICE, REPOR	RT, OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
	ACIDIZE	ALTER CASING	CASING REPAIR	
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME	
1/28/2015	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE	
SUBSEQUENT REPORT	DEEPEN	FRACTURE TREAT	New construction	
Date of Work Completion:	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK	
	l <u></u>			
SPUD REPORT	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	☐ RECOMPLETE DIFFERENT FORMATION	
Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	LI TEMPORARY ABANDON	
	L TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL	
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION	
	WILDCAT WELL DETERMINATION	OTHER	OTHER:	
12. DESCRIBE PROPOSED OR	COMPLETED OPERATIONS. Clearly show a	I pertinent details including dates, o	depths, volumes, etc.	
Newfield proposes	to extend the Application for	Permit to Drill this well.		
			Warhubiyis@n20f15 Oil, Gas and Mining	
			Date:	
			By: Dagyll	
NAME (PLEASE PRINT) Mandie Crozier	PHONE NUMBE 435 646-4825	R TITLE Regulatory Tech		
SIGNATURE N/A		DATE 1/12/2015		

Sundry Number: 59800 API Well Number: 43013528050000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013528050000

API: 43013528050000 **Well Name:** GMBU 3-4-9-17

Location: 1949 FNL 1988 FWL QTR SENW SEC 04 TWNP 090S RNG 170E MER S

Company Permit Issued to: NEWFIELD PRODUCTION COMPANY

Date Original Permit Issued: 1/28/2014

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

3
 If located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes No
 Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
 Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? Yes No
 Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? Yes No
• Has the approved source of water for drilling changed? 🔵 Yes 🌘 No
 Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? 🌘 Yes 💭 No
Signature: Mandie Crozier Date: 1/12/2015
Title: Regulatory Tech Representing: NEWFIELD PRODUCTION COMPANY

Form 3160-3 (August 2007)

UNITED STATES RECEIVED DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0136 Expires July 31, 2010

Lease Serial No. UTU75038

APPLICATION FOR PERMIT	TO DRILL OR RE	ENTER	M	6. If Indian, Allottee or Tri	be Name
1a. Type of Work: DRILL REENTER				7. If Unit or CA Agreemer GREATER MONUN	nt, Name and No. MENT
1b. Type of Well: ☑ Oil Well ☐ Gas Well ☐ Otl	ner 🔀 Sing	le Zone	Multiple Zone	8. Lease Name and Well N GMBU 3-4-9-17	lo.
2. Name of Operator Contact:	MANDIE CROZIER			9. API Well No.	
NEWFIELD EXPLORATION E-Mail: mcrozie	r@newfield.com			43-013-5290	5
3a. Address ROUTE #3 BOX 3630 MYTON, UT 84052	3b. Phone No. (included Ph: 435-646-482) Fx: 435-646-3031	5		10. Field and Pool, or Expl MONUMENT BUTT	oratory
4. Location of Well (Report location clearly and in accorda	ince with any State requi	rements.*)		11. Sec., T., R., M., or Blk.	and Survey or Area
At surface SENW 1949FNL 1988FWL	-			Sec 4 T9S R17E M	er SLB
At proposed prod. zone NENW Lot 3 658FNL 1981	FWL		,		
14. Distance in miles and direction from nearest town or post APPROXIMATELY 12.3 MILES SOUTHEAST C	office* OF MYTON, UT			12. County or Parish DUCHESNE	13. State UT
15. Distance from proposed location to nearest property or	16. No. of Acres in Le	ase		17. Spacing Unit dedicated	to this well
lease line, ft. (Also to nearest drig. unit line, if any) 658'	535.31		ECENTE	40.00	
18. Distance from proposed location to nearest well, drilling,	19. Proposed Depth	į,	EUEIVEL	20. BLM/BIA Bond No. or	ı file
completed, applied for, on this lease, ft. 1320'	6530 MD 6380 TVD	Jl	JN 0 5 2015	WYB000493	
21. Elevations (Show whether DF, KB, RT, GL, etc. 5164 GL	22. Approximate date 08/31/2014	work will start DIV. OF	OIL, GAS & M	23. Estimated duration NING	:
	24. Atta	chments	:		
The following, completed in accordance with the requirements o	f Onshore Oil and Gas O	rder No. 1, shal	l be attached to th	nis form:	
 Well plat certified by a registered surveyor. A Drilling Plan. A Surface Use Plan (if the location is on National Forest Syst SUPO shall be filed with the appropriate Forest Service Off 	em Lands, the acce).	Item 20 at 5. Operator of	oove). certification r site specific info	ormation and/or plans as may	
25. Signature (Electronic Submission)	Name (Printed/Typed) MANDIE CROZ	IER Ph: 43	35-646-4825		Date 01/23/2014
Title REGULATORY ANALYST					
Approved by (Signature)	Name (Printed/Typed)	Jerry	Kenczk	a	JUN 0 2 201
Assistant Field Manager Lands & Mineral Resources	Office VER	NAL FIEL	D OFFICE		
Application approval does not warrant or certify the applicant ho operations thereon.	lds legal or equitable title	•	<u>-</u>	se which would entitle the ap	plicant to conduct
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, n				make to any department or ag	ency of the United

Additional Operator Remarks (see next page)

Electronic Submission #233144 verified by the BLM Well Information System For NEWFIELD EXPLORATION, sent to the Vernal Committed to AFMSS for processing by LESLIE BUHLER on 01/27/2014 ()

NOTICE OF APPRUVAL

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.





UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

VERNAL FIELD OFFICE VERNAL, UT 84078

(435) 781-4400



CONDITIONS OF APPROVAL FOR APPLICATION FOR PERMIT TO DRILL

Company:

Newfield Exploration Company

170 South 500 Fast

Location:

SENW, Sec. 4, T9S, R17E

Well No:

3-4-9-17

Lease No:

UTU-75038

API No:

43-013-52805

Agreement:

UTU-87538X

OFFICE NUMBER:

(435) 781-4400

OFFICE FAX NUMBER: (435) 781-3420

A COPY OF THESE CONDITIONS SHALL BE FURNISHED TO YOUR FIELD REPRESENTATIVE TO INSURE COMPLIANCE

All lease and/or unit operations are to be conducted in such a manner that full compliance is made with the applicable laws, regulations (43 CFR Part 3160), and this approved Application for Permit to Drill including Surface and Downhole Conditions of Approval. The operator is considered fully responsible for the actions of his subcontractors. A copy of the approved APD must be on location during construction, drilling, and completion operations. This permit is approved for a two (2) year period, or until lease expiration, whichever occurs first. An additional extension, up to two (2) years, may be applied for by sundry notice prior to expiration.

NOTIFICATION REQUIREMENTS

Location Construction (Notify Environmental Scientist)	- Forty-Eight (48) hours prior to construction of location and access roads.
Location Completion (Notify Environmental Scientist)	- Prior to moving on the drilling rig.
Spud Notice (Notify Petroleum Engineer)	- Twenty-Four (24) hours prior to spudding the well.
Casing String & Cementing (Notify Supv. Petroleum Tech.)	 Twenty-Four (24) hours prior to running casing and cementing all casing strings to: <u>blm_ut_vn_opreport@blm.gov</u>
BOP & Related Equipment Tests (Notify Supv. Petroleum Tech.)	- Twenty-Four (24) hours prior to initiating pressure tests.
First Production Notice (Notify Petroleum Engineer)	 Within Five (5) business days after new well begins or production resumes after well has been off production for more than ninety (90) days.

SURFACE USE PROGRAM CONDITIONS OF APPROVAL (COAs)

- All new and replacement internal combustion gas field engines of less than or equal to 300 designrated horsepower must not emit more than 2 gms of NO_x per horsepower-hour. This requirement does not apply to gas field engines of less than or equal to 40 design-rated horsepower.
- All and replacement internal combustion gas field engines of greater than 300 design rated horsepower must not emit more than 1.0 gms of NO_x per horsepower-hour.
- If there is an active Gilsonite mining operation within 2 miles of the well location, operator shall notify the Gilsonite operator at least 48 hours prior to any blasting during construction.
- If paleontological materials are uncovered during construction, the operator is to immediately stop
 work and contact the Authorized Officer (AO). A determination will be made by the AO as to what
 mitigation may be necessary for the discovered paleontologic material before construction can
 continue.

Minerals and Paleontology

- If there is an active Gilsonite mining operation within 2 miles of the well location, operator shall notify the Gilsonite operator at least 48 hours prior to any blasting during construction.
- If paleontological materials are uncovered during construction, the operator is to immediately stop work and contact the Authorized Officer (AO). A determination will be made by the AO as to what mitigation may be necessary for the discovered paleontologic material before construction can continue.

Green River District Reclamation Guidelines

The Operator will comply with the requirements of the *Green River District (GRD) Reclamation Guidelines* formalized by Green River District Instructional Memo UTG000-2014-004 on May 21, 2014.

CONDITIONS OF APPROVAL

Wildlife

In accordance with the Record of Decision for the Castle Peak and Eightmile Flat Oil and Gas Expansion Project, Newfield Rocky Mountains Inc., the following COA's are required:

- WFM-1 On level or gently sloping ground (5 percent slope or less) Newfield will elevate surface pipelines (4 inches or greater in diameter) a minimum of 6 inches above the ground to allow passage of small animals beneath the pipe. This ground clearance will be achieved by placing the pipeline on blocks at intervals of 150 to 200 feet.
- WFM-4 Newfield will install noise reduction devices on all pump jacks to reduce intermittent noise to 45 dBA at 660 feet from the source.

COA's derived from mitigating measures in the EA:

If construction and drilling is anticipated during any of the following wildlife seasonal spatial restrictions, a BLM biologist or a qualified consulting firm biologist must conduct applicable surveys using an accepted protocol prior to any ground disturbing activities.

- If it is anticipated that construction or drilling will occur during mountain plover nesting season (May 1 – June 15), a BLM biologist will be notified to determine if surveys are necessary prior to beginning operations. If surveys are deemed necessary, depending on the results permission to proceed may or may not, be granted by the BLM Authorized Officer.
- If the surface disturbing activities are planned during the current timing restrictions for the golden eagle (January 1st through August 31st) a survey for nesting golden eagle will be required. Based on the results of the survey, permission to proceed may or may not be granted.

For protection of T&E Fish if drawing water from the Green River

- For areas of fresh water collection, an infiltration gallery will be constructed in a Service
 approved location. An infiltration gallery is basically a pit or trench dug within the floodplain to a
 depth below the water table. Water is drawn from the pit rather than from the river directly. If
 this is not possible, limit pumping within the river to off-channel locations that do not connect to
 the river during high spring flows.
- If water cannot be drawn using the measures above and the pump head will be located in the river channel where larval fish are known to occur, the following measures apply:
 - Avoid pumping from low-flow or no-flow areas as these habitats tend to concentrate larval fished
 - Avoid pumping to the greatest extent possible, during that period of the year when larval fish may be present (see previous bullet); and
 - Avoid pumping, to the greatest extent possible, during the midnight hours (10:00 p.m. to 2:00 a.m.) as larval drift studies indicate that this is a period of greatest daily activity.
 Dusk is the preferred pumping time, as larval drift abundance is lowest during this time.
 - Screen all pump intakes with 3/32-inch mesh material.
- Report any fish impinged on the intake screen to the FWS office (801.975.3330) and the:
 Utah Division of Wildlife Resources
 Northeastern Region
 318 N Vernal Ave.
 Vernal, UT 84078
 (435) 781-9453

Air Quality

All internal combustion equipment will be kept in good working order.

Page 4 of 9 Well: 3-4-9-17 5/26/2015

- Water or other approved dust suppressants will be used at construction sites and along roads, as determined appropriate by the Authorized Officer. Dust suppressant such as magnesium chloride or fresh water may be used, as needed, during the drilling phase.
- Open burning of garbage or refuse will not occur at well sites or other facilities.
- Drill rigs will be equipped with Tier II or better diesel engines.
- Low bleed pneumatics will be installed on separator dump valves and other controllers.
- During completion, no venting will occur, and flaring will be limited as much as possible. Production equipment and gathering lines will be installed as soon as possible.
- Telemetry will be installed to remotely monitor and control production.
- When feasible, two or more rigs (including drilling and completion rigs) will not be run simultaneously within 200 meters of each other. If two or more rigs must be run simultaneously within 200 meters of each other, then effective public health buffer zones out to 200 meters (m) from the nearest emission source will be implemented. Examples of an effective public health protection buffer zone include the demarcation of a public access exclusion zone by signage at intervals of every 250 feet that is visible from a distance of 125 feet during daylight hours, and a physical buffer such as active surveillance to ensure the property is not accessible by the public during drilling operations. Alternatively, the proponent may demonstrate compliance with the 1-hour NO₂ National Ambient Air Quality Standards (NAAQS) with appropriate and accepted near-field modeling. As part of this demonstration, the proponent may propose alternative mitigation that could include but is not limited to natural gas—fired drill rigs, installation of NO_x controls, time/use restrictions, and/or drill rig spacing.
- All new and replacement internal combustion gas field engines of less than or equal to 300 design-rated horse power must not emit more than 2 grams of NO_x per horsepower-hour. This requirement does not apply to gas field engines of less than or equal to 40 design-rated horsepower-hour.
- All new and replacement internal combustion gas field engines of greater than 300 design rated horsepower must not emit more than 1.0 grams of NO_x per horsepower-hour.
- Green completions will be used for all well completion activities where technically feasible.

Threatened and Endangered Plants

- All subcontractors associated with this Project will be notified of the appropriate conservation measurements associated with this Project.
- Newfield will perform ground disturbing activities in Sclerocactus ssp. Core Conservation
 Areas (CCAs) outside of the flowering period, (April 1 through May 30) for all three well pads.
 This applies to all ground disturbance, including previously disturbed areas on existing well
 pads.
- Access roads, buried pipeline ROWs, well pads, and other facilities requiring removal of vegetation (e.g., compressor stations) will be located a distance of 300 feet from individual Sclerocactus plants and/or populations.

Page 5 of 9 Well: 3-4-9-17 5/26/2015

- The size of the disturbance on the well pad will be reduced to the minimum size needed to meet safety requirements.
- Only water (no chemicals, reclaimed production water or oil field brine) will be used for dust abatement measures within all cactus habitats.
- Dust abatement will be employed in suitable *Sclerocactus ssp.* habitat over the life of the project during the time of the year when *Sclerocactus ssp.* species are most vulnerable to dust-related impacts (March through August) within all cactus habitats.
- Vehicle users associated with this Project will travel at low speeds (15 miles per hour) and will reamin on existing roads and proposed right-of-ways (ROWS) at all times for the life of the Project.
- All disturbed areas will be reclaimed with native plant species, or seed mixtures approved by the FWS Utah Field Office.
- Erosion control measures (i.e. silt fencing) will be implemented to minimize sedimentation to Sclerocactus ssp. plants and populations located down slope of proposed surface disturbance activities when working in all cactus habitats.
- Application for Pesticide Use Permit will include provisions for mechanical removal, as opposed to chemical removal, for Utah Class A, B and C noxious weeds within 50 feet of individual/populations of Sclerocactus.
- Any noxiou/invasive weeds present within 50 ft of the edge of surface disturbance will be controlled using mechanical or spot treatment methods. The FWS Utah Field Office will be notified prior to any noxious weed control activities other than mechanical methods.
- Noxious weeds within Sclerocactushabitat may be controlled wit herbicides, in accordance
 with e BLM Herbicide PEIS (http://www.blm.gov/wo/st/en/prog/more/veg_eis.html) Guidelines
 and the BLM's Standard Operation Procedures for Threatened and Endangered Plant
 Species.
- From one year of the date forward of 100% Sclerocactus clearance survey for this project, spot checks will be conducted and approved for all planned disturbance areas on an annual basis. (The S. brevispinus survey period is defined as mid-March to June 30, and the S. wetlandicus survey period is defined as anytime without snow cover.) Results of spot checks may require additional pre-construction plant surveys as directed by the BLM. If the proposed action or parts thereof have not occurred within four years of the original survey, 100% clearance re-survey will be required prior to ground disturbing activities.
- Newfield will mitigate surface disturbance within the CCA2, by contributing a monetary amount to the SclerocactusMitigation Fund-BLM to aid in the recovery of Sclerocactusspecies impacted by the Project. A total of \$5,446.20 will be contributed to the SclerocactusMitigation Fund-BLM, based on 0.87 acres of disturbance within Sclerocactus CCA2 where current disturbance is over 5%, and mitigation costs of \$6,200/acre (Table 1.). This payment amount is calculated using the SclerocactusHabitat Value Spradsheet in the

2014 Ecological Restoration Mitigation Calculation Guidelines for Impacts to Sclerocactus wetlandicusand Sclerocactus brevispinusHabitat (USFWS 2014b).

Acres Disturbed		Cost per Acre Sclerocactus habitat	Total
	0.87	\$6,260	\$5,446.20

Payment will be made prior to construction. Newfield will include a confirmation of payment in the 48 hour notice. Payment will be paid to:

Sclerocactus Mitigation Fund-BLM
Michelle Olsen, Manager
Impact-Directed Environmental Accounts
National Fish and Wildlife Foundation
1133 Fifteenth St. NW Suite 1100
Washington, DC 20005

Discovery Stipulation: Re-initiation of Section 7 consultation with the USFWS will be sought immediately if any loss of plants or occupied habitat for Pariette cactus or Uinta Basin hookless cactus is anticipated as a result of project activities.

DOWNHOLE PROGRAM CONDITIONS OF APPROVAL (COAs)

SITE SPECIFIC DOWNHOLE COAs:

 Newfield Production Company shall adhere to all referenced requirements in the SOP (version: "Greater Monument Butte Green River Development Program", Feb 16, 2012). The operator shall also comply with applicable laws and regulations; with lease terms Onshore Oil and Gas Orders.
 NTL's; and with other orders and instructions of the , authorized officer.

All provisions outlined in Onshore Oil & Gas Order #2 Drilling Operations shall be strictly adhered to. The following items are emphasized:

DRILLING/COMPLETION/PRODUCING OPERATING STANDARDS

- The spud date and time shall be reported orally to Vernal Field Office within 24 hours of spudding.
- Notify Vernal Field Office Supervisory Petroleum Engineering Technician at least 24 hours in advance of casing cementing operations and BOPE & casing pressure tests.
- All requirements listed in Onshore Order #2 III. E. Special Drilling Operations are applicable for air drilling of surface hole.
- Blowout prevention equipment (BOPE) shall remain in use until the well is completed or abandoned. Closing unit controls shall remain unobstructed and readily accessible at all times. Choke manifolds shall be located outside of the rig substructure.
- All BOPE components shall be inspected daily and those inspections shall be recorded in the daily
 drilling report. Components shall be operated and tested as required by Onshore Oil & Gas Order
 No. 2 to insure good mechanical working order. All BOPE pressure tests shall be performed by a
 test pump with a chart recorder and <u>NOT</u> by the rig pumps. Test shall be reported in the driller's

log.

- BOP drills shall be initially conducted by each drilling crew within 24 hours of drilling out from under the surface casing and weekly thereafter as specified in Onshore Oil & Gas Order No. 2.
- Casing pressure tests are required before drilling out from under all casing strings set and cemented in place.
- No aggressive/fresh hard-banded drill pipe shall be used within casing.
- Cement baskets shall not be run on surface casing.
- The operator must report all shows of water or water-bearing sands to the BLM. If flowing water is
 encountered it must be sampled, analyzed, and a copy of the analyses submitted to the BLM Vernal
 Field Office.
- The operator must report encounters of all non oil & gas mineral resources (such as Gilsonite, tar sands, oil shale, trona, etc.) to the Vernal Field Office, in writing, within 5 working days of each encounter. Each report shall include the well name/number, well location, date and depth (from KB or GL) of encounter, vertical footage of the encounter and, the name of the person making the report (along with a telephone number) should the BLM need to obtain additional information.
- A complete set of angular deviation and directional surveys of a directional well will be submitted to the Vernal BLM office engineer within 30 days of the completion of the well.
- While actively drilling, chronologic drilling progress reports shall be filed directly with the BLM,
 Vernal Field Office on a weekly basis in sundry, letter format or e-mail to the Petroleum Engineers until the well is completed.
- A cement bond log (CBL) will be run from the production casing shoe to the top of cement and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.
- Please submit an electronic copy of all other logs run on this well in CD (compact disc) format to the Vernal BLM Field Office. This submission will supersede the requirement for submittal of paper logs to the BLM.
- There shall be no deviation from the proposed drilling, completion, and/or workover program as approved. Safe drilling and operating practices must be observed. Any changes in operation must have prior approval from the BLM Vernal Field Office.

Page 8 of 9 Well: 3-4-9-17 5/26/2015

OPERATING REQUIREMENT REMINDERS:

- All wells, whether drilling, producing, suspended, or abandoned, shall be identified in accordance with 43 CFR 3162.6. There shall be a sign or marker with the name of the operator, lease serial number, well number, and surveyed description of the well.
- For information regarding production reporting, contact the Office of Natural Resources Revenue (ONRR) at www.ONRR.gov.
- Should the well be successfully completed for production, the BLM Vernal Field office must be
 notified when it is placed in a producing status. Such notification will be by written communication
 and must be received in this office by not later than the fifth business day following the date on
 which the well is placed on production. The notification shall provide, as a minimum, the following
 informational items:
 - o Operator name, address, and telephone number.
 - Well name and number.
 - Well location (¼¼, Sec., Twn, Rng, and P.M.).
 - Date well was placed in a producing status (date of first production for which royalty will be paid).
 - o The nature of the well's production, (i.e., crude oil, or crude oil and casing head gas, or natural gas and entrained liquid hydrocarbons).
 - The Federal or Indian lease prefix and number on which the well is located; otherwise the non-Federal or non-Indian land category, i.e., State or private.
 - Unit agreement and/or participating area name and number, if applicable.
 - Communitization agreement number, if applicable.
- Any venting or flaring of gas shall be done in accordance with Notice to Lessees (NTL) 4A and needs prior approval from the BLM Vernal Field Office.
- All undesirable events (fires, accidents, blowouts, spills, discharges) as specified in NTL 3A will be reported to the BLM, Vernal Field Office. Major events, as defined in NTL3A, shall be reported verbally within 24 hours, followed by a written report within 15 days. "Other than Major Events" will be reported in writing within 15 days. "Minor Events" will be reported on the Monthly Report of Operations and Production.
- Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (BLM Form 3160-4) shall be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3162.4-1. Two copies of all logs run, core descriptions, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, shall be filed on BLM Form 3160-4. Submit with the well completion report a geologic report including, at a minimum, formation tops, and a summary and conclusions. Also include deviation surveys, sample descriptions, strip logs, core data, drill stem test data, and results of production tests if performed. Samples (cuttings, fluid,

and/or gas) shall be submitted only when requested by the BLM, Vernal Field Office.

- All off-lease storage, off-lease measurement, or commingling on-lease or off-lease, shall have prior written approval from the BLM Vernal Field Office.
- Oil and gas meters shall be calibrated in place prior to any deliveries. The BLM Vernal Field Office
 Petroleum Engineers will be provided with a date and time for the initial meter calibration and all
 future meter proving schedules. A copy of the meter calibration reports shall be submitted to the
 BLM Vernal Field Office. All measurement facilities will conform to the API standards for liquid
 hydrocarbons and the AGA standards for natural gas measurement. All measurement points shall
 be identified as the point of sale or allocation for royalty purposes.
- A schematic facilities diagram as required by Onshore Oil & Gas Order No. 3 shall be submitted to the BLM Vernal Field Office within 30 days of installation or first production, whichever occurs first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed in accordance with Onshore Oil & Gas Order No. 3.
- Any additional construction, reconstruction, or alterations of facilities, including roads, gathering
 lines, batteries, etc., which will result in the disturbance of new ground, shall require the filing of a
 suitable plan and need prior approval of the BLM Vernal Field Office. Emergency approval may be
 obtained orally, but such approval does not waive the written report requirement.
- No location shall be constructed or moved, no well shall be plugged, and no drilling or workover
 equipment shall be removed from a well to be placed in a suspended status without prior approval
 of the BLM Vernal Field Office. If operations are to be suspended for more than 30 days, prior
 approval of the BLM Vernal Field Office shall be obtained and notification given before resumption
 of operations.
- Pursuant to Onshore Oil & Gas Order No. 7, this is authorization for pit disposal of water produced from this well for a period of 90 days from the date of initial production. A permanent disposal method must be approved by this office and in operation prior to the end of this 90-day period. In order to meet this deadline, an application for the proposed permanent disposal method shall be submitted along with any necessary water analyses, as soon as possible, but no later than 45 days after the date of first production. Any method of disposal which has not been approved prior to the end of the authorized 90-day period will be considered as an Incident of Noncompliance and will be grounds for issuing a shut-in order until an acceptable manner for disposing of said water is provided and approved by this office.
- Unless the plugging is to take place immediately upon receipt of oral approval, the Field Office Petroleum Engineers must be notified at least 24 hours in advance of the plugging of the well, in order that a representative may witness plugging operations. If a well is suspended or abandoned, all pits must be fenced immediately until they are backfilled. The "Subsequent Report of Abandonment" (Form BLM 3160-5) must be submitted within 30 days after the actual plugging of the well bore, showing location of plugs, amount of cement in each, and amount of casing left in hole, and the current status of the surface restoration.

Sundry Number: 69093 API Well Number: 43013528050000

			1	
STATE OF UTAH			FORM 9	
	DEPARTMENT OF NATURAL RESOURCE DIVISION OF OIL, GAS, AND MINI	5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-75038		
SUNDRY NOTICES AND REPORTS ON WELLS			6. IF INDIAN, ALLOTTEE OR TRIBE NAME:	
	oposals to drill new wells, significantly d reenter plugged wells, or to drill horizon n for such proposals.		7.UNIT or CA AGREEMENT NAME: GMBU (GRRV)	
1. TYPE OF WELL Oil Well			8. WELL NAME and NUMBER: GMBU 3-4-9-17	
2. NAME OF OPERATOR: NEWFIELD PRODUCTION CO	OMPANY		9. API NUMBER: 43013528050000	
3. ADDRESS OF OPERATOR: Rt 3 Box 3630 , Myton, UT		PHONE NUMBER: Ext	9. FIELD and POOL or WILDCAT: MONUMENT BUTTE	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1949 FNL 1988 FWL			COUNTY: DUCHESNE	
QTR/QTR, SECTION, TOWNS	HIP, RANGE, MERIDIAN: 04 Township: 09.0S Range: 17.0E Meridi	an: S	STATE: UTAH	
11. CHEC	K APPROPRIATE BOXES TO INDICAT	E NATURE OF NOTICE, REPOR	RT, OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
7	ACIDIZE	ALTER CASING	CASING REPAIR	
A / O O / O O A C	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME	
1/28/2016	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE	
SUBSEQUENT REPORT	DEEPEN [FRACTURE TREAT	☐ NEW CONSTRUCTION	
Date of Work Completion:	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK	
	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION	
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON	
	TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL	
☐ DRILLING REPORT	WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION	
Report Date:	WILDCAT WELL DETERMINATION	OTHER	OTHER:	
12. DESCRIBE PROPOSED OR	COMPLETED OPERATIONS. Clearly show al	Il pertinent details including dates.	depths, volumes, etc.	
I .	to extend the Application for			
			-	
			Date:	
			By: Dally	
NAME (PLEASE PRINT)	PHONE NUMBE			
Mandie Crozier	435 646-4825	Regulatory Tech		
SIGNATURE N/A		DATE 1/13/2016		

Sundry Number: 69093 API Well Number: 43013528050000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013528050000

API: 43013528050000 Well Name: GMBU 3-4-9-17

Location: 1949 FNL 1988 FWL QTR SENW SEC 04 TWNP 090S RNG 170E MER S

Company Permit Issued to: NEWFIELD PRODUCTION COMPANY

Date Original Permit Issued: 1/28/2014

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

• If located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes No
 Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
• Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? Yes No
• Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? Yes No
• Has the approved source of water for drilling changed? Yes No
 Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? Yes No
nature: Mandie Crozier Date: 1/13/2016

Sig

Title: Regulatory Tech Representing: NEWFIELD PRODUCTION COMPANY

Sundry Number: 77418 API Well Number: 43013528050000

STATE OF UTAH			FORM 9	
	DEPARTMENT OF NATURAL RESOURCE DIVISION OF OIL, GAS, AND MINI	5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-75038		
SUNDRY NOTICES AND REPORTS ON WELLS			6. IF INDIAN, ALLOTTEE OR TRIBE NAME:	
	oposals to drill new wells, significantly d reenter plugged wells, or to drill horizon n for such proposals.		7.UNIT or CA AGREEMENT NAME: GMBU (GRRV)	
1. TYPE OF WELL Oil Well			8. WELL NAME and NUMBER: GMBU 3-4-9-17	
2. NAME OF OPERATOR: NEWFIELD PRODUCTION CO	OMPANY		9. API NUMBER: 43013528050000	
3. ADDRESS OF OPERATOR: Rt 3 Box 3630 , Myton, UT		PHONE NUMBER: Ext	9. FIELD and POOL or WILDCAT: MONUMENT BUTTE	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1949 FNL 1988 FWL			COUNTY: DUCHESNE	
QTR/QTR, SECTION, TOWNSI Qtr/Qtr: SENW Section: (HIP, RANGE, MERIDIAN: 04 Township: 09.0S Range: 17.0E Meridia	an: S	STATE: UTAH	
11. CHEC	K APPROPRIATE BOXES TO INDICATE	NATURE OF NOTICE, REPOR	RT, OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
	ACIDIZE [ALTER CASING	CASING REPAIR	
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME	
1/28/2017	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE	
SUBSEQUENT REPORT	DEEPEN [FRACTURE TREAT	New construction	
Date of Work Completion:	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK	
	l —			
SPUD REPORT	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION	
Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	☐ TEMPORARY ABANDON	
	L TUBING REPAIR	UENT OR FLARE	WATER DISPOSAL	
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION	
	WILDCAT WELL DETERMINATION	OTHER	OTHER:	
12. DESCRIBE PROPOSED OR	COMPLETED OPERATIONS. Clearly show al	l pertinent details including dates, o	depths, volumes, etc.	
Newfield proposes	to extend the Application for	Permit to Drill this well.		
			Warnubiyisib,n20fl 7 Oil, Gas and Mining	
			Date:	
			By: Bally Still	
NAME (DI EACE DOINT)	DUONE NUMBE	D TITLE		
NAME (PLEASE PRINT) Mandie Crozier	PHONE NUMBE 435 646-4825	R TITLE Regulatory Tech		
SIGNATURE N/A		DATE 1/9/2017		

Sundry Number: 77418 API Well Number: 43013528050000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43013528050000

API: 43013528050000 Well Name: GMBU 3-4-9-17

Location: 1949 FNL 1988 FWL QTR SENW SEC 04 TWNP 090S RNG 170E MER S

Company Permit Issued to: NEWFIELD PRODUCTION COMPANY

Date Original Permit Issued: 1/28/2014

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

• If located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes No
Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
• Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? Yes No
• Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? Yes No
• Has the approved source of water for drilling changed? Yes No
 Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? Yes No
nature: Mandie Crozier Date: 1/9/2017

Sig

Title: Regulatory Tech Representing: NEWFIELD PRODUCTION COMPANY